

## Parker 1048 & 1348 Specifications

| MODEL                       | 1048               | 1348  |
|-----------------------------|--------------------|---|
| Capacity*                   | 1,000 + bushels    | 1,300 bushels                                   |
| Height - Unloading side     | 12' 5"             | 12' 5"  |
| Height-Loading side         | 11' 5"             | 11' 5"  |
| Width-Cart                  | 11' 11"            | 11' 10"   |
| Track width                 | 11' 4"             | 120" Singles<br>60"/120" or<br>70"/144" Tandems |
| Length-Tongue to hub        | 17' 4"             | 19' 11"   |
| Width-Overall cart          | 14' 4"             | 15' 4" Singles<br>12'/14" Tandems               |
| With 76-or 68-50.00x32      | 16' 2"             | 15' 4"  |
| Auger-Reach                 | 8' 5"              | 8' 3"   |
| Auger-Unloading height      | 13' 7"             | 13' 10"   |
| Clearance                   | 1' 3"              | 1' 11"  |
| Tongue Height               | 1' 7"              | 1' 9"   |
| Length-Overall              | 26' 9"             | 32' 3"  |
| Length-Box                  | 18' 8"             | 23' 10"   |
| Weight (empty) lbs.         | 12,050             | 18,710  |
| Tongue Weight (loaded) lbs. | 5,500              | 5,800   |
| Auger Size                  | 18"                | 22"   |
| Tires (standard)            | 900/60 X 32 R-3    | 76/50.00 x 32                                   |
| Spindle Dia.**- Singles     | 3-3/4"             | 5-1/2"  |
| Duals and 68x50.00x32       | 4-1/2"             | 3-3/4" Tandems                                  |
| Standard Hitch              | Single             | Single  |
| PTO Yoke, Std.              | 1-3/4" X 20 Spline | 1-3/4" x 20 Spline                              |

### Loaded PSI

The following chart illustrates the relative ground pressure calculated at the 3" soil penetration level. These charts are useful as a comparative guide for the various undercarriage options available by model.

|                   |       |       |
|-------------------|-------|-------|
| 35.5 x 32         | 18.60 | —     |
| 900/60 x 32       | 25.49 | —     |
| 1050/50 x 32      | 17.00 | —     |
| 76-50.00 x 32     | 15.51 | 22.01 |
| 380/90 x 46       | —     | —     |
| Duals 520/85 x 42 | 16.01 | 24.06 |
| Duals 480/80 x 46 | 18.02 | —     |
| Tracks            | 10.41 | 13.29 |

\* Capacity reflects #2 corn with 56# test weight

\*\* Constructed of special alloy steel for greatest strength